



GraeL LT EEG

# ® graeL LT

Industry-leading value amplifier with research-grade technology.

A DC-coupled, digital amplifier system with a high input range and 22-bit resolution providing amplification and digitization of electroencephalographic physiologic signals. The amplifier provides 39 channels (32 isolated high-frequency referential channels, 6 bipolar channels) and event button input. The unit has a POE 100BASE-TX network connection for both power and communication.

HD EEG

OVER  DECADES OF ADVANCED  
BRAIN RESEARCH

# Technical specifications



**INPUTS** 32, DC-coupled, fully isolated, referential (monopolar); 6 user-defined, DC-coupled, fully isolated, bipolar inputs

**INPUT IMPEDANCE** >100 M $\Omega$  1-32;  
>20 M $\Omega$  33-40

**BIAS CURRENT** typically 1nA

**INPUT NOISE** < 2  $\mu$ Vpp typical (referential ch)

**INPUT RANGE** 600mVpp

**CMRR** > 100dB

**CROSSTALK** <- 60dB to adjacent channels FSR

**HIGH PASS FILTER** DC Coupled

**LOW PASS FILTER** (3dB):  
71 Hz at 256 s/s  
143 Hz at 512 s/s  
284 Hz at 1024 s/s  
580 Hz at 2048 s/s

**NOTCH FILTER** Software based display filtering of 50Hz, 60Hz, or off

**ISOLATION SPECIFICATIONS**  
Complies with IEC 60601-1 CF patient Inputs

**ANALOGUE TO DIGITAL CONVERTER**  
22 bit resolution

**SAMPLE AND DATA RATES CHANNELS 1 TO 40**  
Data sampled at 16384 samples per second and decimated to data rates shown below. Actual data rate sent is determined by controlling PC software application.

**Output data rate** 2048, 1024, 512 or 256 samples per second

**COMMUNICATION INTERFACE**  
**Network Type** 802.3/802.3u twisted pair Ethernet with auto MDIX; RJ45 connector.

**EVENT BUTTON CHANNEL x 1**

## DIMENSIONS

Graef EEG System Component	Size L x W x H	Weight
Amplifier	240mm x 144mm x 50mm 9.45in x 5.66in x 1.97in	700 grams 24.7 ounces

## ENVIRONMENTAL REQUIREMENTS

**Temperature** Ambient operating temperature range:  
0°C - 40°C (32°F - 104°F)  
Storage temperature range:  
-10°C - 50°C (-4°F - 122°F)

**Humidity** 20% - 90%-relative humidity (non-condensing)

**Altitude** Less than 3,000m

## ELECTRICAL SPECIFICATIONS

**Power Supply** All power provided by the network connection using Power Over Ethernet (either mid-span injector or POE Switch, per IEEE 802.3af standard)

**Operating voltage** 48 volts

**Power consumption** <10 watts

## For more information please contact:

**Compumedics Limited, Australia:**  
**Headquarters**  
30-40 Flockhart Street  
Abbotsford VIC 3067, Australia  
Ph: +61 3 8420 7300  
Fax: +61 3 8420 7399  
Free Call: 1800 651 751

**Compumedics USA, Inc.:**  
5015 West WT Harris Blvd, Suite E  
Charlotte, NC 28269  
Toll Free: +1 877 717 3975  
Ph: +1 704 749 3200  
Fax: +1 704 749 3299

**Compumedics Germany GmbH:**  
Global HQ for Compumedics DWL  
Josef-Schüttler-Strasse 2  
D-78224 Singen, Germany  
Ph: +49 7731 79 76 9-0  
Fax: +49 7731 79 76 9-99

All specifications are subject to change without notice. Please contact your Compumedics representative for latest technical information, pricing and product availability. Graef, COMPUMEDICS and the Compumedics logo are registered trademarks of Compumedics.

[www.compumedics.com](http://www.compumedics.com)

